



# SEASNAKE 12.7

**The remote-controlled weapon station SEASNAKE 12.7 is a new member of the innovative Rheinmetall product line of the latest generation for self-protection in close and immediate range for a variety of classes of surface units, even under the most difficult operating conditions. The modular concept enables the integration of different upgrade kits for the installation of weapons in caliber 5.56 x 45 mm to 12.7 x 99 mm or GMW 40 mm.**

The integrated vision system (FlexEye®) represents the latest day and night vision (IR) sensor technology and thus enables the simultaneous, weather-independent display of several targets.

Using the latest image processing algorithms, movements of the barrel axis, caused by ballistics, can be compensated and allows for a coaxial assembly on a 2-axis stabilized platform. In addition to manual target tracking, a powerful tracker also enables automatic target tracking.

All data relevant for fire control are processed in real time and provides the system with a high level of precision that is relevant to the application and performance.

The use of standard interfaces (e.g. NGVA) simplifies the system's integration into various classes of naval vessels

The carbon-based mount technology enables a consequent reduction in weight and vibration, which, in conjunction with the shape and design, offers a significantly reduced signature.

The weapon station sets standards in the areas of protection class, operational capability and dynamic targeting of asymmetrical threats due to the cross-sectional use of innovative software modules within the latest Rheinmetall Remote Control Weapon Systems.

The combination of an intuitive operating concept and intelligent assistance systems represents a noticeable relief for the operator in combat situations. The SEASNAKE 12.7 weapon system has the ability to integrate additional operating consoles and also meets the safety requirements of IEC 61508.

## PERFORMANCE FEATURES

- High First-Hit Probability
- High angular precision and speed
- Ability to fight dynamically
- Automatic Target Tracking
- Self-stabilized platform
- Possibility of integration into a CMS
- Light weight, low signature
- No deck penetration required
- Optonic cleaning system
- NGVA-Interface
- Fitted for ROSY, AGDUS, ballistic protection
- IEC 61508 / MIL-STD-810H
- ITAR-free

## MONITOR

- Infrared-Touchscreen
- Military hardening
- Suitable for night-time operations



## JOYSTICK

- Ergonomic design
- Left- or right handed operable
- Individually configurable
- Complete operating redundancy



## TECHNICAL DATA & DIMENSIONS

Height	≈ 870 mm
Length	≈ 1.770 mm
Width	≈ 970 mm
Weight (empty, incl. Flex-Eye®-Sensor)	≈ 136 kg
Weight (empty, incl. Weapon)	≈ 174 kg
Weight (total, incl. Weapon /200 rounds)	≈ 200 kg
Azimuth	n x 360°
Elevation	-20° to +60°
Max. angular speed	120°/s
Max. angular acceleration	≥ 120°/s <sup>2</sup>

## WEAPON ADAPPTIONS

Cannon	M2-Browning HMG, Caliber 12.7 mm x 99
Cannon	MG-5A1 (H&K), Caliber 7.62 mm x 51
Grenade launcher	GMW (H&K), Caliber 40 mm x 53

## SENSOR DATA FLEX-EYE

<b>IR camera</b>	SAPHIR / UC 5.9
Spectral band	8 -12 μm
Detector	640 x 480
FoV 1	5.9°
FoV 2	25.3°
Range within FoV 1 i.a.w. STANAG 4347 σ=0.2	Identification > 1.500m Recon > 2.820m Detection > 7.590m
<b>Color camera 1</b>	CMOS
Spectral band	Visible
Sensor	2.064 x 1.544
FoV	6.7°
Range within FoV VR=23km	Identification > 2.700m Recon > 5.330m Detection > 12.580m
<b>Color camera 2</b>	CMOS
Spectral band	Visible
Sensor	2.064 x1.544
FoV	23.75°
<b>Laser Range Finder</b>	Diode Laser
Range / Wave length	≥10.000 m / ~1.55μm
Frequency / Accuracy (1σ)	25 Hz / < 1m
Classification (IEC60825-1 2014)	1

Note: The scope of supply, appearance, performances, dimensions and weights of the system correspond to the knowledge available at the time of printing. Deviations from the illustrations in color and form, errors and misprints as well as changes are reserved.