

Product	KINS.0114 Q T13 C01
Material Composition	UHMW-PE
Cover Material	Cordura®, black
Protection Level	VPAM BSW 2006 Level 6+ (stand-alone) 3 shots 7.62 x 39 FMJ/PB/FeC (PS) 3 shots 7.62 x 51 FMJ/PB/SC (DM111) incl. angle shots
Areal Weight <i>Tolerance ± 4 %</i>	12,3 kg/m ²
Thickness <i>Tolerance ± 1 mm</i>	14,0 mm
Shape / Curvature	Torso / Back Plate (SAPI L, multi-curved)
Dimensions Width x Length (Protected Area) <i>Tolerance ± 3 mm</i>	258 x 335 mm ² (835 cm ²)
Weight (incl. Cover) <i>Tolerance ± 5 %</i>	1,03 kg

Remarks

Changes due to technical improvements are possible. This information corresponds with the latest available technology and is offered without liability.

Instructions for Use / Storage

Handle insert carefully and protect it against hard impacts. Don't stack or place weight on insert. Don't expose insert to temperatures higher than 70°C.

Maintenance Guide

Inspect and clean insert with water and mild soap at least every 3 month. Don't use any solvent or aggressive detergent. In case of visual damage send insert back to the manufacturer.

Version 02/2024

